# Your international partner www.trexrubber.com



## **T-REX Tools**

Tools to make the job easier, on site or in the workshop

#### **BUFFING TOOLS**

√ T-REX buffing tools for grinding rubber surfaces

#### **Copper Flat Discs**

Diameter 125 x 2 mm AH 22 mm, K18

Diameter 125 x 2 mm AH 22 mm, K23

Diameter 175 x 2 mm AH 22 mm, K18

Diameter 175 x 2 mm AH 22 mm, K23





#### **Copper Unit Wheels**

Diameter 102 x 38 mm AH 14 mm, K18





#### **COLD SPLICE ROLLER**

- ✓ Aluminium, lighter than steel
- √ Strong design
- √ Great pressure

CSR 600 mm

CSR 800 mm

Belt width up to 1.100 mm

Belt width up to 1.500 mm

CSR 1.000 mm

Belt width up to 2.200 mm



#### **REX-CLAMP**

- ✓ Stripping conveyor belt (removal of rubber covers, fabric/ steel cables for splicing
- ✓ Pulling conveyor belts togeter for quick repair/installation
- **√** 1.500 kg
- √ Strong design



### **T-REX Tools**

Tools to make the job easier, on site or in the workshop

#### **BELT LIFTING STATION**

- ✓ It reduces risk for injury when placing splicing station or change rollers.
- ✓ Made of lightweight aluminium, easy to transport.
- ✓ Suitable for belt width between 650 mm to 1.000 mm.

Length 1.150 mm Width 315 mm Weight 14,9 kg



#### **HAND TOOLS**

001 Offset flexible knife (to cut uncured rubber)

002 Rubber knife

003 Round brush

004 Ply lifter

005 Pointed stitcher 4 mm

006 Stitcher, smooth 12 mm

007 Cylindrical stitcher 45 mm

Needle stitcher (to perforate cushion gum) 27 mm

009 Curved hand rasp (to buff rubber surface)

010 "Quarter moon" knife

004

005

006

007

008

009